

## PENDING CLAIMS AS AMENDED

Please amend the claims as follows:

---

1-9 (canceled)

10. (currently amended) A method in a wireless communication system, comprising:  
designating a multi-carrier forward link having a plurality of forward link frequency bins;  
and  
designating a reverse link having at least one reverse link frequency bin,  
wherein the forward link frequency bins and the at least one reverse link frequency bin  
are designated such that bandwidth of the forward link can be allocated differently from  
bandwidth of the reverse link.

E 11. (previously presented) The method of claim 10 further comprising:  
selecting a first forward link frequency bin from the plurality of forward link frequency  
bins for forward link transmission, the first forward link frequency bin having an associated first  
reverse link frequency bin; and  
selecting a second reverse link frequency bin for reverse link transmission corresponding  
to the forward link transmission wherein the second reverse link frequency bin is different from  
the first reverse link frequency bin.

12. (previously presented) The method of claim 11 wherein the selecting a second  
reverse link frequency bin is based on loading of the system.

13. (previously presented) The method of claim 11, further comprising:  
selecting a third reverse link frequency bin for reverse link transmission corresponding to  
the forward link transmission, wherein the third reverse link frequency bin is different from the  
first and second reverse link frequency bins.

14. (previously presented) The method in accordance with claim 10, wherein said plurality of forward link frequency bins comprise three frequency bins.

15. (previously presented) The method in accordance with claim 10, wherein said plurality of forward link frequency bins are adjacent frequency bins.

16. (previously presented) The method in accordance with claim 11, wherein said multi-carrier forward link is adapted for transmission of a plurality of code channels, wherein one of said plurality of code channels is used to communicate power control information for said second reverse link frequency bin.

17. (~~currently~~ amended) A method of allocating bandwidth for forward and reverse link transmissions in a wireless communication system, comprising:

receiving communications on a multi-carrier forward link, the multi-carrier forward link having a plurality of forward link frequency bins, the reverse link having at least one frequency bin,

wherein the forward link bins and the at least one reverse link frequency bins are configured such that the allocation of bandwidth for the forward and reverse link transmissions can be varied.

18. (previously presented) The method of claim 17, further comprising:

receiving by a first device a communication on a forward link frequency bin, the forward link frequency bin having an associated first reverse link frequency bin; and

transmitting by a second device via a second reverse link frequency bin, wherein said second reverse link frequency bin is different from the first reverse link frequency bin.

19. (previously presented) The method as in claim 18, further comprising:

receiving by the first device an indication of a reverse link frequency bin.

20. (previously presented) An apparatus in a wireless communication system, comprising:

a first means for transmitting information on a multi-carrier forward link, wherein said multi-carrier forward link comprises a plurality of forward link frequency bins; and

a second means for designating a reverse link frequency bin, wherein said first and second means configure the frequency bins so as to enable differential allocation of bandwidth for forward link and reverse link transmissions.

21. (previously presented) The apparatus of claim 20, further comprising:

means for selecting a first forward link frequency bin from the plurality of forward link frequency bins for the forward link transmission, the first forward link frequency bin having an associated first reverse link frequency bins; and

means for selecting a second reverse link frequency bin for the reverse link transmission corresponding to the forward link transmission, wherein the second reverse link frequency bin is different from the first reverse link frequency bin.

22. (previously presented) The method of claim 10, wherein the designations of the forward and reverse link includes allocating more bandwidth for the forward link than the reverse link.

23. (previously presented) The method of claim 10, wherein the designation of the forward link includes configuring the forward link as a cdma2000 3X forward link.

24. (previously presented) The method of claim 23, wherein the forward link includes first, second, and third carriers.

25. (previously presented) The method of claim 24, wherein said first, second, and third carriers occupy first, second, and third adjacent frequency bins, respectively.

26. (previously presented) The method of claim 25, wherein the designation of the reverse link includes configuring the reverse link as a cdma2000 1X reverse link.

27. (previously presented) The method of claim 26, wherein the reverse link includes a fourth carrier.

28. (~~currently~~ amended) The method of claim 27, wherein the fourth carrier is located in a frequency range ~~substantially~~ similar to the second frequency bin.

---